for safe storage

PRODUCT DATA SHEET

CEMO Centri SP 30 submersible pump for diesel, 12 V, 50 L/min (max.)

Order no.: 91000

PRODUCT DESCRIPTION

- low-cost entry-level solution
- self-priming as submersible pump on container bottom
- low-wear centrifugal pump for reliable operation
- electric motor with max. 18 A power consumption
- user-friendly handling
- compact, lightweight design
- external pump dimensions: length 160 mm, dia. 56 mm
- extremely quiet



TECHNICAL DATA

External dimensions (lxh)	5.6 x 5.6 x 21 cm
Weight	0.65 kg
Pump drive	Pump
Pump model	Centrifugal pump
Max. flow rate	50 L/min (max.)
Operating voltage	12 V
Max. electrical power	280 W
Max. delivery pressure	1.1 bar (max.)
Connection on pressure side	Hosetail DN 19
Warranty in years	1
Assembly condition	mounted
Plug	without

EQUIPMENT

Connection on pressure side	Hosetail DN 19

SUITABLE STORAGE MEDIA

Diesel
AdBlue®
Biodiesel
HVO
XTL
Heating oil
Brine
Water
Antifreeze fluid

LOGISTICS

Package dimensions (l x w x h)	26 x 18 x 20 cm
Units per box	1
Units per pallet	2
Pallet dimensions	26 x 18 x 20 cm
Shipping weight	1 kg
Freight	Parcel service
Customs tariff number	84137021

ACCESSORIES



90958 - Cable switch cpl. 16A / 250V, bipolar



91026 - Connector cable, isolated, length: 4 m with clamps a. fuse 25A,2x flat plug 6,3

Technical specifications subject to change/Errors and omissions excepted. © CEMO 91000-en 10.26
CEMO GmbH | In den Backenländern 5 | 71384 Weinstadt | Germany | Tel. +4971519636-0 | kontakt@cemo-group.com