for safe storage

PRODUCT DATA SHEET

DT-Mobil Easy 125 l, 12V, CENTRI SP30 25 l/min, automatic nozzle

Order no.: 10606

PRODUCT DESCRIPTION

- certified for transport for direct consumption according to ADR 1.1.3.1 c)
- single-walled container made from robust polyethylene
- dispensing nozzle holder keeps everything clean and tidy
- integral filler neck for easy filling
- ventilation with pressure relief for improved safety
- forklift pockets and ergonomic handles for convenient loading
- recesses for ratchet straps for securing during transport



TECHNICAL DATA

Content volume	125 l
External dimensions (lxh)	80 x 60 x 45 cm
Weight	20 kg
Use	mobile
Place of installation	Transport
Material	LLDPE
Coating	uncoated
Container colour	grey
Operating voltage	12 V DC
Pump drive	Pump
Max. flow rate	25 L/min (max.)
Dispensing hose length	4 m
Hose diameter	DN 19
Stackable	yes
ADR instruction	according to ADR 1.1.3.1 c)
Dispensing nozzle	Automatic diesel

Cable length	4
Warranty in years	2
Assembly condition	mounted
Plug	Crocodile clips

EQUIPMENT

Forklift pockets	yes

SUITABLE STORAGE MEDIA

Diesel
Biodiesel
HVO
Heating oil

LOGISTICS

Package dimensions (l x w x h)	80 x 60 x 52 cm
Units per box	1
Units per pallet	8
Pallet dimensions	120 x 80 x 220 cm
Shipping weight	35 kg
Freight	General cargo
Customs tariff number	84137021

ACCESSORIES



8644 - Digital flow metre K24 (Cematic pumps) for Cematic pumps



8963 - Lid for Mobile Easy 125L and 200L



10229 - Plug DIN 9680, 3-pin, 6-24 V, max. 25A, IP54



10230 - Socket DIN 9680, 3-pin, 6-24V, max.25A, IP54



10953 - Anti-slip mat 800 x 1200 x 3 mm



11111 - Digital flow meter K24 (210L,440L,Combi) for DT-Mobile Easy 210, 440,Combi 440/50

Technical specifications subject to change/Errors and omissions excepted. © CEMO 10606-en 10.26
CEMO GmbH | In den Backenländern 5 | 71384 Weinstadt | Germany | Tel. +4971519636-0 | kontakt@cemo-group.com